



Wall saw WSE1621 MKII

Cutting depths up to 705 mm



Even more powerful drive motor with low-wear clutch and tool-free motor mounting



New blade guard: robust, tool-free and modular design (same side parts and holders for all sizes)



Compact control unit, handy radio remote control with screen


The WSE1621 MKII is a further development of the WSE1621 and is characterised in particular by increased power, ergonomics and reliability. The new P2[®] drive motor has a noticeably higher torque and ensures more power and maximum productivity, even

with larger blade diameters. New All-in-one blade guards combine stability with a simple, tool-free control panel and a wide range of functions, such as flush cutting or dry cutting. The modular, expandable concept enables further applications such as ring

or wire sawing, as well as drilling, which saves space and mounting times as well as costs. In addition, the compact and lightweight components with quick locks make daily use on the construction site easier for the user.



System & Accessories



Technical data

Saw blade	
Max. cutting depth	705 mm
Max. saw blade Ø	1 600 mm
Free detachable up to Ø	900 mm
Blade flange mounting	Quick-release flange
Saw blade fixing (flush cuts)	Part circle 130 mm: M8 countersunk head screws x 6 pcs. Pitch circle 110 mm: M10 countersunk head screws x 6 pcs.

Electric motor

Water-cooled high-frequency motor P2® Technology	
Nominal power (32 A)	21 kW
Motor power S1 (32 A)	19 kW
Voltage	400–480 V
Frequency	50 / 60 Hz

Weight

Wall saw WSE1621 MKII	24 kg
WSE1621 MKII main electric motor	16 kg
WSE1621 MKII control unit	18 kg
Remote control WSE1621 MKII	1.8 kg
Blade guard 1025 mm AIO MKII	26 kg
VAS G 1100 mm rail	9.4 kg
VAS G rail 1650 mm	15
VAS G 1 rail 925 mm	16.2 kg
VAS G 2 rail 200 mm	18.4 kg
Transport trolley WSE1621 MKII	27 kg

Service contracts

11014804	WSE1621 MKII BASIC Service contract
11014805	WSE1621 MKII STANDARD Service contract
11014806	WSE1621 MKII PREMIUM Service contract

System & Accessories

Wall saw system WSE1621 MKII	
11008300	Wall saw WSE1621 MKII
11008400	WSE1621 MKII electric main motor 400–480 V / 50 Hz
11008500	WSE1621 MKII electric control unit 400–480 V / 50 Hz incl. radio remote control
11012856	Transport trolley WSE1621 MKII
11012858	Blade guard 1025 mm AIO MKII
10982079	VAS G rail 1100 mm aluminium
109818	VAS G rail 2200 mm aluminium
977523	Track joint VAS and VS rail
965987	V-rail feet aluminium, flat
10980346	Tool box

Accessories

11012857	Blade guard 825 mm AIO MKII
11012859	Blade guard 1200 mm AIO MKII
977606	Blade guard 1600 mm 2-piece
10998282	Blade guard holder 1600 mm
11010891	Blade guard holder AIO MKII
10977882	Quick release flange
961983	V-swivel rail bracket
10977452	V rotary rail support
10981719	Small transport trolley WX
10999403	Blade flange ST dry cut
11007376	Service case WSE1621