



Shot blaster FBE560

Working width 560 mm



Perfect blast patterns with 6-bladed blastwheel



The drive unit ensures consistent and even feed



FBE560 maintenance and tool box

The FBE560 shot blaster is a professional blasting system for large areas, very hard concrete floors or coatings and steel. Compact, reliable, powerful and manouverable, low height and up to 37 kW power. Made for blasting middle sized or big areas. Maximum blast performance in combination with a low frame height. The FBE560 is easy to transport and

has long life wear and tear parts. The drive unit enables an even and infinitely adjustable feed. Available also as FBE560P2 with a 15 kW or the FBE560P3 with an 18.5 kW motor. Maintenance work on the shot blaster can be carried out easily on site and without the use of special tools, thus saving time and operating costs.



System & Accessories

Technical data

Shot blaster	FBE560	FBE560P2
Type no.	11009335	11009336
Reference model Contec	ELGATOR	ELGATOR
Voltage / Frequency	400 V / 50 Hz	
Working width	500 mm	
Nominal power	2 x 11 kW	2 x 15 kW
Nominal current	43 A	55 A
Speed (drive motor)	2935 rpm	
Application	Dry	
Hose connection	Ø 150 mm	
Recommended vacuum cleaner	VCE7522C, VCE5522C	

Design

Variable drive unit for forward and backward motion	•	•
Brake assist for working on ramps	•	•
LED headlights	•	•
Operating hours counter	•	•
Foldable rear axle for transport	•	•

Dimensions & weight

Length	1850 mm	
Width	750 mm	
Height	1150 mm	
Weight	650 kg	690 kg

Accessories

11009394	Service box incl. tools and wear parts FBE560
11004035	Magnetic brush 50 cm
11002991	Magnetic brush 70 cm
11002992	D125 hose anti static, 15 m
11004022	Blast wheel set FBE300/350/500/560 + cage
11009353	Side lining blast chamber FBE560
11011757	Top lining blast chamber FBE560
11004682	Steel shot S 390 F20 VE 25 kg
11004684	Steel shot S 460 F16 VE 25 kg
11018779	Magnetic work LED