



Floor grinder FGE250M1

Universal grinder for concrete, asphalt, wood and steel, max. grinding width 250 mm



Equipped with interchangeable tool bracket



Variety of tool segments for all applications



Folds down easily to fit in a car trunk

The FGE250M1 is a universal machine for concrete, asphalt, wood, steel and formwork. Outstandingly versatile, this all-rounder grinder performs many different operations, combining impressive high performance with low weight. The simple design of the FGE250M1 ensures easy operation. The handlebar can be quickly

adjusted for operator comfort and control. Noise and vibration levels are minimal during normal operation. The compact dimensions and low weight allow it to pass through all doors and be transported to every floor level, even onto a balcony. The FGE250M1 can grind within a few millimeters of a wall. Use with a

Tyrolit dust extractor for clean, low-dust and safe operation.

System & Accessories

Technical data

Floor grinder	FGE250M1 230 V	FGE250M1 110 V
Type no.	11009338	11017275
Reference model Contec	OMEGA	OMEGA
Voltage / Frequency	230 V / 50 Hz	110 V / 50 Hz
Max. grinding width	250 mm	
Grinding heads	1 x 250 mm	
Nominal power	2 kW	1.5 kW
Nominal current	13 A	18.7 A
Grinding speed	1460 rpm	
Motor cooling	Air	
Application	Dry / wet	
Tool attachment	Grinding plate 250 mm	
Number of tools	1 x 6 pieces	
Hose connection	Ø 50 mm	
Recommended vacuum cleaner	VCE2400D, VCE3600D, VCE1200D	

Design

1 grinding disc	•
Flexible coupling	•

Dimensions & weight

Length	900 -1030 mm
Width	330 mm
Height	900-1000 mm
Weight	58 kg

Accessories

34705213	1 piece tool holder Ø 250 mm for 6 tools 1 piece is needed
11018779	Magnetic work LED