




Shaver FPE340


Working width 340 mm



Cutting depths of up to 50 mm are possible



The cutting depth is changed by lowering the milling drum electrically



Specially manufactured diamond discs can be fitted to cutter drums

The FPE340 is made for the hardest applications and floors. Heavy duty bearings ensure maintenance and trouble-free operation of the machine. The continuously variable speed drive unit is a standard.

Ergonomically designed handle bars ensure fatigue-free operation. With our diamond cutter drums and

a working width of 340 mm, this machine is ideal for processing large areas, slatted floors and walkways which increase slip resistance (grooving).

System & Accessories

Technical data

Shaver	FPE340
Type no.	11011026
Reference model Contec	CT 340
Voltage / Frequency	400 V / 50 Hz
Working width	340 mm
Nominal power	18.5 kW (2 x 0.18 kW)
Nominal current	33.4 A
Speed (drive motor)	2935 rpm (3000 rpm)
Motor cooling	Air
Application	Dry / wet
Hose connection	Ø 125 mm, connection tube
Recommended vacuum cleaner	VCE7522C, VCE5522C

Design

Variable speed drive unit	•
Variable cutting width	•
Follow-up suction device	•
Protective cover	•

Dimensions & weight

Length	1530 mm
Width	7400 mm
Height	1 140 mm
Weight	480 kg

Accessories

11002731	Exchangeable drum for diamond blades (without blades)
34540058	Diamond blade 300 mm FSC premium
11002735	Spacer 1 mm for diamond drum
11002734	Spacer 2 mm for diamond drum
11002733	Spacer 3 mm for diamond drum
11003371	Spacer 5 mm for diamond drum
11003372	Spacer 8 mm for diamond drum
11018779	Magnetic work LED